


RoHS Compliant








REVISION HISTORY

REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		

MATERIAL / SPECIFICATION	
Rating	DC12V 50mA
Travel	0.25±0.1mm
Operating Force	250±30gf
Contact Resistance	50mΩ Max
Life	100,000 Cycles Min
BOM: Cover Plate	Iron
BOM: Cap	PA66; Color Black
BOM: Spring Leaf	Stainless Steel
BOM: Base	PA66; Color Black
BOM: Insert	Brass; Color Silver Plated

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
0~3	±0.1
3~6	±0.15
6~9	±0.2
9~12	±0.25
12~15	±0.3

PROJECTION



THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	Tactile Switch Side 3 Pin Through-Hole						
PART NO.	KS-TS-X-15					REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1