

RoHS Compliant


REVISION HISTORY

REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		







SECTION A–A




RECOMMENDED PCB LAYOUT

TOP VIEW







MATERIAL / SPECIFICATION	
Current rating	1.0 A
Voltage rating	12 V
Dielectric withstand	500 V
Contact resistance	30mΩ MAX
Insulation resistance	500MΩ
Operating temperature	−40°C ~ +85°C
Housing material	LCP, black
Contact material	Copper alloy
Contact area plating	Gold 3 µin

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
X.	±0.35
X.X	±0.25
X.XX	±0.15
X.XXX	±0.05
PCB .XX	±0.05

PROJECTION

THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	1.6 mm Pitch 1.4 mm Height SMT Spring Contact Battery Connector (4 Pin) Top-Contact						
PART NO.	KS-BC160-04T-140					REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1