

RoHS Compliant


REVISION HISTORY				
REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		







RECOMMENDED PCB LAYOUT

T=1.2MM, TOLERANCES ±0.05MM







MATERIAL / SPECIFICATION	
Housing	PA9T, UL 94V-0
Terminal	C2680
Underplate	Nickel 50 u" min. overall
Area plating	Au on contact or Tin on soldering area
Current rating	5 A
Voltage rating	30 V AC
Dielectric strength	500 VAC
Insulation resistance	100 MΩ min.
Contact resistance	30 mΩ max.
Operating temperature	-40° to 105°

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
X.	0.5
X.x	0.35
X.xx	0.25
ANGULAR	2

PROJECTION

THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	Large 2 mm Pitch Vertical Through-Hole Male Blade Battery Connector (11 Pin)						
PART NO.	KS-BL200-11M-VD					REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1