


RoHS Compliant


REVISION HISTORY				
REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		





MATERIAL / SPECIFICATION	
Current rating	0.5 A
Voltage rating	50 V
Dielectric withstand	500 V
Contact resistance	30mΩ
Insulation resistance	500MΩ
Operating temperature	−20°C ~ +85°C
Housing material	LCP
Contact material / finish	Phosphor bronze, gold plated





PCB Layout

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
.X	±0.2
.XX	±0.05
.XXX	±0.005
ANGLE .X	±0.1°
ANGLE .XX	±0.05°
ANGLE .XXX	±0.005°

PROJECTION

THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	2.54 mm Pitch 3.5 mm Height SMT Spring Contact Battery Connector (6 Pin) Top-Contact						
PART NO.	KS-BC254-06T-350					REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1