



RoHS Compliant


REVISION HISTORY				
REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		













MATERIAL / SPECIFICATION	
Note	The SMD lead length of our company has three types: one is 8.0±0.2, another is 8.5±0.2, another is 9.0±0.2; please note the distinction.
Rating	DC12V 50mA
Travel	0.25±0.1mm
Operating Force	250±30gf
Contact Resistance	50mΩ Max
Life	100,000 Cycles Min
Thermostability	260°C - 280°C
BOM: Cover Plate	Iron; Remark Copper-Tin Plated
BOM: Button	PA6T; Color Black
BOM: Spring Leaf	Silver-Clad Copper; Remark Imported
BOM: Base	PPA; Color Black
BOM: Insert	Brass; Remark Silver Plated


SCHEMATIC





GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
0~3	±0.1
3~6	±0.15
6~9	±0.2
9~12	±0.25
12~15	±0.3

PROJECTION



THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	Tactile Switch 6.2×6.2 4 Pin SMD 4.3H								
PART NO.	KS-TS-TSTP62H							REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1		