

RoHS Compliant


REVISION HISTORY


REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		



MATERIAL / SPECIFICATION	
Housing	HIGH TEMPERATURE THERMOPLASTIC, UL94 V-0
Color	BLACK
Terminal	COPPER ALLOY
Stator	COPPER ALLOY
Plating (contact)	NI UNDERPLATING OVER ALL
Finish (contact area)	GOLD FLASH ON CONTACT AREA








RECOMMENDED PCB LAYOUT

TOLERANCE:±0.05

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
.X	±0.25
.XX	±0.15
.XXX	±0.05
ANGULAR	±1°

PROJECTION



THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	Large 2 mm Pitch 2.5 mm Height SMT Female Blade Battery Connector (4 Pin) With Locating Post						
PART NO.	KS-BL200-04F-S250P					REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1