


RoHS Compliant


REVISION HISTORY				
REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		






MATERIAL / SPECIFICATION	
Insulator	Nylon 9T (UL94V-0)
Contact	Phosphor Bronze
Contact Plating	Gold over Nickel or Tin
Current Rating	5 A
Instant Current	7 A
Contact Resistance	30 mΩ
Insulation Resistance	100 MΩ
Dielectric Voltage	500 V
Operating Temperature	-40° to +105°








Recommended P.C.B Layout

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
X.	±0.20
X.x	±0.10
X.xx	±0.05
ANGULAR	±2°

PROJECTION



THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	Large 2 mm Pitch Right-Angle Through-Hole Male Blade Battery Connector (5 Pin)								
PART NO.	KS-BL200-05M-RD							REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1		