

RoHS Compliant


REVISION HISTORY

REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		






MATERIAL / SPECIFICATION	
Insulator	Nylon 9T (UL94V-0)
Contact	Phosphor Bronze
Contact Plated	Gold over Nickel or Tin
Current Rating	5A
Instant Current	7A
Contact Resistance	30 mΩ
Insulation Resistance	100 MΩ
Dielectric Voltage	500V
Operating Temperature	-40°~105°



PCB Layout



GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
XX.	±5
XX.°	±1°
X.	±0.5
X.°	±0.5°
.X	±0.2
.X°	±0.25°
.XX	±0.10
.XX°	±0.1°

PROJECTION

THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	Large 2 mm Pitch 9.85 mm Height Right-Angle Through-Hole Female Blade Battery Connector (5 Pin) With Locating Post						
PART NO.	KS-BL200-05F-RD985P					REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1