


RoHS Compliant

REVISION HISTORY				
REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		








PCB Layout Dimensions




Schematic









MATERIAL / SPECIFICATION	
Rating	50mA DC12V
Insulation Resistance	⩾100 MΩ (DC100V)
Dielectric Strength	AC100V(50/60Hz for 1 minute)
Mechanical Life	10,000 cycles
Operating Temperature	-10°C~+60°C
Operating Force	200±100gf
Material Property	Environmentally Friendly (SGS)
BOM: Cover	Qty 1; Stainless Steel; Silver White
BOM: Contact Spring	Qty 4; Phosphor Bronze; Silver White, Silver Plated
BOM: Button	Qty 1; Reinforced Nylon; Black
BOM: Base	Qty 1; LCP & Brass; Black & Silver Plated

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	PROJECTION	DRAWN BY	KANGSHENG
	THIRD ANGLE PROJECTION	CHECKED BY	
		APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	Slide Switch 12 Pin SMD 15×3.5						
PART NO.	KS-SS-15035-S					REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1