


RoHS Compliant

REVISION HISTORY


REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		









MATERIAL / SPECIFICATION	
Rated Load	DC12V 50mA
Insulation Resistance	⩾100 MΩ
Dielectric Strength	AC250V 50Hz/1min
Electrical Life	10000 cycles min
Operating Temperature	-25~+70°C
Relative Humidity	(40°C) ⩽95%
Contact Resistance	⩽70 mΩ
Operating Force	180gf±50gf
BOM: Spring	Qty 1; Stainless Steel; Silver White
BOM: Contact Spring	Qty 1; Silver-Clad Copper; Silver White Inlaid Silver
BOM: Cover	Qty 1; Stainless Steel; Silver White
BOM: Base	Qty 1; LCP; Black & Silver Plated
BOM: Handle	Qty 1; High-Temp Nylon; Black







GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	PROJECTION	DRAWN BY	KANGSHENG
	THIRD ANGLE PROJECTION	CHECKED BY	
		APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	Slide Switch 4 Pin SMD With Locating Post Silent							
PART NO.	KS-SS-SK-06C						REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1	