


RoHS Compliant


REVISION HISTORY				
REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		







DIM A	DIM B
7.0	5.0
10.5	8.5
14.0	12.0
17.5	15.5
21.0	19.0
24.5	22.5
28.0	26.0









RECOMMENDED PCB LAYOUT

TOP VIEW(.XX±0.05)

MATERIAL / SPECIFICATION	
Current Rating	5.0A
Voltage Rating	30V
Dielectric Withstanding Voltage	500V
Contact Resistance	30 mΩ max.
Insulation Resistance	500 MΩ
Operating Temperature	-55℃~+125℃
Durability	10000 cycles min.
Insulator	LCP
Color	Black
Contact	Brass C2680
Contact Plated	Gold 3μ" on contact surface

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
X.	±0.35
X.X	±0.25
X.XX	±0.15
X.XXX	±0.05

PROJECTION

THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	3.5 mm Pitch 1.9 mm Height SMT Female Spring Contact Battery Connector (2–8 Pin) With Locating Post							
PART NO.	KS-BC350-04F-190P-NN						REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1	