


RoHS Compliant

REVISION HISTORY


REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		









MATERIAL / SPECIFICATION	
Current rating	5.0 A
Voltage rating	30 V
Dielectric withstand	500 V
Contact resistance	30mΩ
Insulation resistance	500MΩ
Operating temperature	−55°C ~ +125°C
Housing material	PA9T Black
Contact material	Brass C2680
Contact area plating	Gold
Durability	10000 cycles MIN







RECOMMENDED PCB LAYOUT

TOP VIEW

DIMENSION		
PINS	DIM A	DIM B
2	4.0	2.0
3	6.0	4.0
4	8.0	6.0
5	10.0	8.0
6	12.0	10.0
7	14.0	12.0
8	16.0	14.0

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
X.	±0.35
X.X	±0.25
X.XX	±0.15
X.XXX	±0.05
PCB .XX	±0.05

PROJECTION

THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	2 mm Pitch 1.27 mm Height SMT Female Spring Contact Battery Connector (2–8 Pin) With Locating Post								
PART NO.	KS-BC200-03F-127P-NN							REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1		