
RoHS Compliant


REVISION HISTORY

REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		





ALL SOLDERTAIL&PEG

⌭	0.10



DIMENSION		
HEIGHT	DIM A	DIM B
5.4	5.4	4.4
6.0	6.0	4.7
7.0	7.0	5.6
8.0	8.0	6.7





RECOMMENDED PCB LAYOUT

TOP VIEW(.XX±0.05)

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
X.	±0.15
X.X	±0.10
X.XX	±0.05
X.XXX	±0.005
ANGLE X.	±1°
ANGLE X.X	±0.5°
ANGLE X.XX	±0.05°
ANGLE X.XXX	±0.005°
PCB .XX	±0.05

PROJECTION

THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	2.5 mm Pitch 5.4~8.0 mm Height SMT Spring Contact Battery Connector (3 Pin) No Locating Post Side-Contact								
PART NO.	KS-BC250-03S							REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1		