

RoHS Compliant

REVISION HISTORY


REV.	DESCRIPTION	DRAWN BY	CHECKED BY	APPROVED BY
A0	INITIAL RELEASE	KANGSHENG		







Recommended P.C.B Layout

Layout Tolerance: ±0.05 mm







MATERIAL / SPECIFICATION	
Insulator	Nylon 9T (UL94V-0) (C5191EH)
Contact	Phosphor Bronze
Contact Plating	Gold over Nickel or Tin
Current Rating	3 A
Instant Current	5 A
Contact Resistance	30 mΩ
Insulation Resistance	100 MΩ
Dielectric Voltage	500 V
Operating Temperature	-40° to +105°

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
X.	±0.20
X.X	±0.15
X.XX	±0.10
ANGULAR	±2°

PROJECTION

THIRD ANGLE PROJECTION

DRAWN BY	KANGSHENG
CHECKED BY	
APPROVED BY	

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

PRODUCT NAME	1.5 mm Pitch Right-Angle Through-Hole Female Blade Battery Connector (8 Pin)						
PART NO.	KS-BL150-08F-RD					REV.	A0
SCALE	NTS	UNIT	mm	SIZE	A3	SHEET	1/1