









Recommended P.C.B Layout

Layout Tolerance=+/-0.05mm

Material
Insulator:Nylon 9T(UL94V-0)(C2680EH)
Contact:phosphor Bronze
Contact Plated:Gold over Nickel or Tin
Specification
Current rating:3A
instant CURRENT:5A
Contact Resistance:30M?
Insulation Resistance:100M?
Dielectric Voltage:500V
Operating Temperature:-40°~105°

No. of Pins	Dimension		
	DIM.A	DIM.B	DIM.C
02	4.50	3.50	1.50
03	6.00	5.00	3.00
04	7.50	6.50	4.50
05	9.00	8.00	6.00
06	10.50	9.50	7.50
07	12.00	11.00	9.00
08	13.50	12.50	10.50
09	15.00	14.00	12.00
10	16.50	15.50	13.50
11	18.00	17.00	15.00
12	19.50	18.50	16.50
13	21.00	20.00	18.00
14	22.50	21.50	19.50
15	24.00	23.00	21.00
16	25.50	24.50	22.50

深圳市康生电子科技有限公司
Shenzhen Kangsheng Electronic Technology Co., Ltd.

UNLESS OTHERWISE SPECIFIED, TOLERANCE:
X. ±0.20 ANGULAR ±2°
X.X ±0.15
X.XX ±0.10

DESIGN		DATE		TITLE: 电池连接器
APPROVED		DATE		
MODEL: 1.5间距180度公座系列		REV:	SCALE:	UNIT: mm
		SIZE: A4	SHEET: 1/1	